Actigrip HP

DESCRIPTION
- Industrial protective glove.
- Nitrile supported glove.
- Elastic wrist.
- 2 versions :
- Actigrip HP : Tropique 3/4 dipped,
- ActigripHP Elastofix : fully dipped.
- 4 sizes available : 7, 8, 9 and 10.
- Trade unit: 10 pairs, 150 pairs in a transit case.

CHARACTERISTICS
- Lightweight 13 gauge seamless knitted glove.
- Made from high performance fibre, using Techcor® Knitting Technology.
- Nitrile coating with rough finish.
- Latex knit wrist to ensure snug fit.

PERFORMANCES
- Excellent abrasion and cut resistance.
- Very good grip properties, especially of slippery oily parts.
- High degree of flexibility and confort in use.
- Coating resistant to residual oils and greases.
- In conformity with the standard EN420 (General requirements) and EN388 (Mechanical Hazards) by the Institut Français Textile-Habillement.

APPLICATIONS
- For all handling of parts in slightly polluted environment
- Ideal for use in automotive, glazing and areas with high cut risks.

LIMITATIONS
- Do not use for handling liquids or pointed objects.
- Do not use with a rotating machine in which glove may get caught.

This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.

CE

EN 420

EN 420
5 Dexterity

3341

EN 388
Mechanical hazards

EN 388
3 Abrasion
3 Cut
4 Tear
1 Puncture

Order codes

Sizes	**7**	**8**	**9**	**10**
Actigrip HP	18FXE01000	18FXE02000	18FXE03000	18FXE04000
Actigrip HP Elastofix	18FXE91000	18FXE92000	18FXE93000	18FXE94000

www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com